



PLAN VIEW

Scale: 1" = 30"

PRESS-SEAL GASKET CORP.
 "EZ-WRAP" Rubber External
 Joint Sealing, 6" Min. Width
 Or Approved Equal
 (Typical, All Adjustment Ring
 And Manhole Joints)

Press-Seal Gasket Corporation
 Or Approved Equal Preformed
 Butyl Joint Sealant. Minimum
 Bead Dimensions = Two-1"
 Or One-2" Beads Per Joint
 (Typical, All Joints)

American Step Company, Inc.,
 ML-13 Or Approved Equal

Deeter Foundry, Inc.
 #1315
 Or Approved Equal

Reinf. To Be
 In Accordance
 With Loading
 Requirements

MANHOLE SECTION A

Scale: 1" = 30"

REINFORCEMENT: Steel Wire, Plain ASTM A-82
 : Welded Wire, ASTM A-185
 : (Area .18 in. sq./ft.)
 : 5 Bars @ 6" Centers EW

Precast Manhole Sections Meet or Exceed the Requirements of ASTM C-478

CONCRETE: 4000psi A.E.

PRETECH CORPORATION provides this digital document with the intention of providing the most current information available at the time of this production.

72" ID MANHOLE WITH REDUCER

San
 72 WR