



- SIZE -	LENGTH			WIDTH						WEIGHT / lbs.	Cubic Yards	T / G
	- A -	- B -	A + B	- C -	- D -	2C + D	- E -	- F -	- G -			
15"	43"	30.5"	6'- 1½"	2.25"	30"	2'-10½"	8.25"	3"	2.25"	2,000 lbs.	0.50 CY	4"
18"	46"	27"	6'- 1"	2.5"	36"	3'- 5"	11.5"	3.5"	2.5"	2,450 lbs.	0.60 CY	4"
24"	36"	37"	6'- 1"	3"	48"	4'- 6"	12.5"	4"	3"	3,050 lbs.	0.75 CY	4"
30"	19"	53"	6'- 0"	3.5"	60"	5'- 7"	15.5"	5"	3.5"	5,050 lbs.	1.25 CY	4"
36"	34.75"	62.25"	8'- 1"	4"	72"	6'- 8"	19"	6"	4"	6,450 lbs.	1.60 CY	4"
42"	35.25"	62.25"	8'- 1½"	4.5"	78"	7'- 1"	25.5"	6.5"	4.5"	10,000 lbs.	2.50 CY	4"
48"	26"	71"	8'- 1"	5"	84"	7'-10"	29"	7.25"	5"	13,000 lbs.	3.25 CY	4"
54"	35"	62"	8'- 1"	5.5"	90"	8'- 5"	32.5"	8"	5.5"	17,200 lbs.	4.30 CY	4"
60"	39.5"	58"	8'- 1½"	6"	96"	9'- 0"	36"	8.5"	6"	19,200 lbs.	4.80 CY	4.5"
72"	18"	77.25"	7'-11¼"	7.75"	106"	10'-2¼"	48"	7.25"	9"	22,400 lbs.	5.60 CY	5"

END SECTION(S) MANUFACTURED IN ACCORDANCE WITH APPLICABLE PORTIONS OF ASTM SPECIFICATIONS C76

PRETECH
 Precast Concrete Technologies
 Locally Owned & Operated

8934 Woodend Rd.
 Kansas City, KS 66111
 (913) 441-4600

**REINFORCED CONCRETE
 FLARED END SECTION(S)**

Reference
 Only
RP8